


- Technical requirements:**
1. Please use the grease specified by our company
 2. The * in the drawing is the installation reference size, please follow the installation size requirements.
 3. If the product performance parameters are not specified, please refer to the latest catalog of our company for the standard values.

Laifunai

FHT-25-XX-U-1				Model		Reduction ratio		Rated torque at 2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load torque		Permissible maximum momentary torque		Permissible maximum input rotational speed		Permissible average input rotational speed		Backlash	weight	Desian life
MODEL	U	T	W					Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min		r/min		Arc Sec	kg	Hour
								50	39	4	98	10	55	5.6	186	19	5600	3500	≤20			≥10000
								80	63	6.4	137	14	87	8.9	255	26	5600	3500	≤20			≥15000
Wave generator-A ø11	ø11H7	12.8 ^{±1}	4JS9/P9					100	67	6.8	157	16	108	11	284	29	5600	3500	≤20			≥15000
								120	67	6.8	167	17	108	11	304	31	5600	3500	≤20			≥15000
Wave generator-A ø14	ø14H7	16.3 ^{±1}	5JS9/P9					160	67	6.8	176	18	108	11	314	32	5600	3500	≤20			≥15000