




- Technical requirements:**
- 1.Please use the grease specified by our company
 - 2.The * in the drawing is the installation reference size, please follow the installation size requirements.
 - 3.If the product performance parameters are not specified, please refer to the latest catalog of our company for the standard values.

FSS-20-XX-U-I				Model		Reduction ratio	Rated torque at2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load torque		Permissible maximum momentary torque		Permissible maximum input rotational speed		Permissible average input rotational speed		Backlash	weight kg	Desian life Hour
MODEL	U	T	W	Nm	kgfm		Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min	Arc Sec						
Wave generator-A φ8	φ8H7	9.4.8 ^{±1}	3JS9/P9	20	50	25	2.5	56	5.7	34	3.5	98	10	6500	3500	≤20	≥10000				
					80	34	3.5	74	7.5	47	4.8	127	13	6500	3500	≤20	≥15000				
					100	40	4.1	82	8.4	49	5	147	15	6500	3500	≤20	≥15000				
					120	40	4.1	87	8.9	49	5	147	15	6500	3500	≤20	≥15000				
Wave generator-A φ11	φ11H7	12.8 ^{±1}	4JS9/P9		160	40	4.1	92	9.4	49	5	147	15	6500	3500	≤20	≥15000				
Wave generator-A φ14	φ14H7	16.3 ^{±1}	5JS9/P9																		

Laiifuai