




Technical requirements:
 1. Please use the grease specified by our company
 2. The * in the drawing is the installation reference size, please follow the installation size requirements.
 3. If the product performance parameters are not specified, please refer to the latest catalog of our company for the standard values.

Laitual

FSN-32-XX-U-I																					
MODEL		U	T	W																	
Wave generator-A φ14	φ14H7	16.3 ^{±1}	5JS9/P9	Model	Reduction ratio	Rated torque at2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load torque		Permissible maximum momentary torque		Permissible maximum input rotational speed		Backlash	weight	Desian life			
						Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min				Arc Sec	kg	Hour
						50	76	7.8	216	22	108	11	382	39	4800				3500	≤20	≥15000
						80	118	12	304	31	167	17	568	58	4800				3500	≤20	≥15000
						100	137	14	333	34	261	22	647	66	4800				3500	≤20	≥15000
Wave generator-A φ19	φ19H7	21.8 ^{±1}	6JS9/P9	32	100 <td>137</td> <td>14</td> <td>333</td> <td>34</td> <td>261</td> <td>22</td> <td>647</td> <td>66</td> <td>4800</td> <td>3500</td> <td>≤20</td> <td>FSN-I:2.47</td> <td>≥15000</td>	137	14	333	34	261	22	647	66	4800	3500	≤20	FSN-I:2.47	≥15000			
						120	137	14	353	36	261	22	686	70	4800	3500	≤20	≥15000			
						160	137	14	372	38	261	22	686	70	4800	3500	≤20	≥15000			
Wave generator-A φ22	φ22H7	24.8 ^{±1}	6JS9/P9	32	100 <td>137</td> <td>14</td> <td>333</td> <td>34</td> <td>261</td> <td>22</td> <td>647</td> <td>66</td> <td>4800</td> <td>3500</td> <td>≤20</td> <td>FSN-I:2.47</td> <td>≥15000</td>	137	14	333	34	261	22	647	66	4800	3500	≤20	FSN-I:2.47	≥15000			
						120	137	14	353	36	261	22	686	70	4800	3500	≤20	≥15000			
						160	137	14	372	38	261	22	686	70	4800	3500	≤20	≥15000			